```
=> d his


        (FILE 'USPAT' ENTERED AT 10:31:48 ON 28 APR 1999)
L1          353 S (INTERNET) (5A) (PHONE OR TELEPHONE)
L2           33 S L1/AB OR L1/CLM

=> d 1-10


1.  5,884,073, Mar. 16, 1999, System and method for providing technical
support of an electronic system through a web bios; David E. Dent, 713/2
[IMAGE AVAILABLE]

2.  5,884,032, Mar. 16, 1999, System for coordinating communications via
customer ·contact channel changing system using call centre for setting up
the call between customer and an available help agent; Thomas Howard
Bateman, et al., 370/356; 379/201, 209, 216, 265 [IMAGE AVAILABLE]

3.  5,870,723, Feb. 9, 1999, Tokenless biometric transaction
authorization method and system; David Ferrin Pare, Jr., et al., 705/39
[IMAGE AVAILABLE]

4.  5,867,660, Feb. 2, 1999, Method and apparatus for communicating
between a network workstation and an internet; Jonathan Schmidt, et al.,
709/227 [IMAGE AVAILABLE]

5.  5,862,339, Jan. 19, 1999, Client connects to an internet access
provider using algorithm downloaded from a central server based upon
client's desired criteria after disconnected from the server; Patrick P.
Bonnaure, et al., 395/200.57, 200.47, 200.48, 200.49, 200.58 [IMAGE
AVAILABLE]

6.  5,862,202, Jan. 19, 1999, Fax routing system and method using
standard fax machine and personal computer; Joseph Elias Bashoura, et
al., 379/100.14; 358/407, 440; 370/352; 379/100.09, 130 [IMAGE AVAILABLE]

7.  5,860,068, Jan. 12, 1999, Method and system for custom manufacture
and delivery of a data product; David Philip Cook, 705/26; 395/200.47
[IMAGE AVAILABLE]

8.  5,848,143, Dec. 8, 1998, Communications system using a central
controller to control at least one network and agent system; G. Wayne
Andrews, et al., 379/219; 370/270, 352; 379/198, 207, 229, 265 [IMAGE
AVAILABLE]

9.  5,848,137, Dec. 8, 1998, Device and method for processing multimedia
message; Ray-Ling Hsiao, 379/110.01, 93.23, 100.06 [IMAGE AVAILABLE]

10.  5,845,074, Dec. 1, 1998, Smart internet information delivery system
having a server automatically detects and schedules data transmission
based on status of clients CPU; Hiroshi Kobata, 395/200.49; 345/335;
707/10; 709/102, 229, 235 [IMAGE AVAILABLE]
```